

Merion MW

Modular Wavelengths diode-pumped pulsed Nd: YAG laser



MAIN FEATURES

- Lightweight and compact design
- Repetition rates up to 200 Hz
- Quick and easy access to 1064, 532, 355 & 266 nm
- Plug & play harmonics with automatic phase-matching
- Quick-connect cables and cooling lines
- Single longitudinal mode option available
- No installation required
- Diode warranty: 2 billion shots

MAIN APPLICATIONS

**LiDAR · OPO PUMPING-
PHOTOACOUSTIC IMAGING ·
Ti:Sa PUMPING ·
MATERIAL PROCESSING ·
LASER PEENING ·
ABLATION · SPECTROSCOPY ·
LIF · LASER ULTRASOUND ·**


SPECIFICATIONS

		MERION MW 7-100	MERION MW 7-200	MERION MW 9-100
Repetition rate ⁽¹⁾ (Hz)		100	200	100
Energy per pulse (mJ)	1064 nm	300	200	650
	532 nm	160	95	360
	355 nm	90	60	200
Pulse to pulse stability (%) [rms%]	1064 nm	< +/- 2 [0.6]		
Divergence (mrad)	1064 nm	< 1 ⁽²⁾		
Pulse duration (ns)	1064 nm	5-9		
Polarization	1064 nm	Vertical		
Polarization ratio (%)	1064 nm	> 95	> 90	
Cooling		water to air	water to water, chiller as option	
Dimensions in mm [inches] (HxLxW)	laser head	147 x 526 x 125 [5.8 x 20.7 x 4.9]		
	harmonic modules	99 x 143 x 125 [3.9 x 5.6 x 4.9]		
	power supply	177.4 x 482.6 x 457.2 [6.99 x 19 x 18]	537 x 553 x 813 [21.1 x 21.77 x 32]	
Weight in kg [lbs.]	laser head	< 8 [15.4]		
	harmonic modules	< 4 [8.8]		


(1) Other repetition rates on request

(2) Multimode version for flat top spatial profiles on request

Typical beam profiles



Near Field 650 mJ
@1064 nm, 100 Hz



Far Field 650 mJ
@1064 nm, 100 Hz

www.quantel-laser.com

Many options and configurations are available. Please contact Lumibird to find the best match for your needs and compatibility between options.



Lumibird has locations across the globe that are available to provide support for any product, service or inquiry. Visit www.lumibird.com to connect with any of our global sites.

